

**Features:**

- polyethylene container with 35 litres capacity and up to 20 litres switching volume
- built-in waste water pump ZPK with float switch
- connection for air vent and cable gland DN 50 (HT)
- inlet connection piece DN 50 is included - installable by drilling a hole in the container
- pressure outlet 1 1/4" with integrated non-return valve
- operation temperature 40°C (short-term 90°C)
- protection grade IP 68 - fully submersible

**Application:**

- pumping of domestic waste water from washing machines, showers, washbasins etc.
- below-ground installation in frost-free rooms below the backflow level

**Scope of delivery:**


- pre-assembled ready for connection with 10 m power cable and plug
- accessible plastic grade, siphon, sand-trap
- inlet connection piece DN 50
- extended top section and closed cover plate available as accessories


**Product benefits:**

- ready for connection - pump and control unit already integrated
- integrated siphon for prevention of odour nuisance
- pre-drilled additional inlets possible

**Technical data:**

Art.no.	U [V]	P <sub>1</sub> [W]	P <sub>2</sub> [W]	In [A]	n [min <sup>-1</sup> ]	Q <sub>max</sub> [m <sup>3</sup> /h]	H <sub>max</sub> [m]	SH [mm]	P0	Weight [kg]
11513	230	850	430	3,7	2800	11,0	11,0	10	G 1 1/4	7

**Characteristics:**

**Materials:**

Material impeller:	PA6 GV25
Seal motor:	shaft seal NBR
Seal pump:	mechanical seal carbon/ceramic/NBR
Material motor housing:	stainless steel AISI 316L
Material pump housing:	PP GF20
Material motor shaft:	stainless steel AISI 430F
Material container:	PE

**Dimensions:**

