

Features:

- for use behind water softening systems and for calorific value condensate
- sealing by mechanical seal and additional shaft seal ring
- stainless steel motor housing (1.4404), stainless steelmotor shaft
- motor winding with thermal winding protection
- mechanical seal and additional shaft seal
- horizontal pressure outlet 1 1/4" MPT
- version 'A' with mounted float switch
- version 'KS' with mounted compact float switch (fits into pipes with an inner diameter larger than 250 mm)
- protection grade IP 68 – fully submersible



Application:

- drainage of slightly acidic condensate, aggressive or salty media (max. 15% salt content)
- lifting of domestic faecal-free waste water (operation temperature 40°C / short-term up to 90°C)

Scope of delivery:

- pump with 10 m power cable and plug
- 90° hose connecting bend (ZPK 30: DN 25; ZPK 35 and ZPK 40: DN 32)


Product benefits:

- pumping of slightly acidic condensate, aggressive or salty media (max. 15% salt content)
- light and robust version
- 10 mm to 30 mm (S-ZPK 40) solids handling for larger solids available
- double sealing by mechanical seal and additional shaft seal
- integrated thermal winding protection to prevent overheating damage

Technical data:

Art.no.	U [V]	P ₁ [W]	P ₂ [W]	I _n [A]	n [min ⁻¹]	Q _{max} [m ³ /h]	H _{max} [m]	SH [mm]	P0	Onmin [mm]	OFFmin [mm]	D [mm]	H [mm]	Weight [kg]
13034	230	850	430	3,7	2800	11,0	11,0	10	G 11/4	160	25	150	302	6,45

Characteristics:



Materials:

Material impeller:	PA6 GV25
Seal motor:	shaft seal NBR
Seal pump:	mechanical seal carbon/ceramic/Viton
Material motor housing:	stainless steel AISI 316L
Material pump housing:	PP GF20
Material motor shaft:	stainless steel AISI 318LN

Dimensions:

