

Features:

- Self-priming electric centrifugal pump with butt injector, which is able sucking gases solved in the water as well
- With handle
- Self-priming up to 8 m
- Smoothly running
- Suction and pressure connectors, internal thread (1")
- Diffusor and injector from thermoplastic material approved for drinking water
- Stainless steel screw for filling and drainage

Application:

- Water supply for domestic services
- Minor watering installations
- Washing facilities
- Decanting of tanks etc.
- Supply of clear water without aggressive and abrasive components
- Garden irrigation

Scope of delivery:

- Completely wired including mains cable H05 RNF, 1.5 m long, with ON/Off-switch




Product benefits:

- Smooth running
- Stainless steel pump case
- Lifetime-lubricated motor bearings
- Self-priming up to 8 m
- With handle and ON/Off-switch completely wired

Technical data:

Art.no.	U [V]	P _i [W]	I _n [A]	n [min ⁻¹]	Q _{max} [m ³ /h]	H _{max} [m]	PO	L [mm]	W [mm]	H [mm]	Weight [kg]
18562	230	1.000	6,0	2900	3,6	50,0	RP1	354	184	290	11,8

Characteristics:



Materials:

Material impeller:	stainless steel AISI 304
Seal pump:	mechanical seal carbon/ceramic/NBR
Material motor housing:	Light metal L-2521
Material pump housing:	stainless steel AISI 304
Material motor shaft:	stainless steel AISI 316

Dimensions:

