

Features:

- Self-priming, maintenance-free, multi-stage, horizontal centrifugal pump
- High efficiency
- Suction and pressure connectors, internal thread (1" - 1¼")
- CPS SM with ON/OFF-switch
- CPS GG / SM: Grey-cast iron suction and discharge case
- CPS B: Suction and discharge case made of α-brass resistant to dezincification
- Impellers made of fibre-glass reinforced Noryl®

Application:

- Domestic water supply
- Rainwater utilization
- Pressure boost
- Irrigation
- For clear water without aggressive and abrasive components

Scope of delivery:

- Completely wired including mains cable H07 RNF, 1.5 m long, with plug




Product benefits:

- Very smooth and low-noise running
- Outstanding hydraulic capacity
- Lifetime-lubricated motor bearings
- Shaft made of stainless steel 1.4401
- High efficiency - power-saving operation
- Motor of robust industrial quality
- Self-priming up to 8 m

Technical data:

| Art.no. | U [V] | P ₁ [W] | I _n [A] | n [min ⁻¹] | Q _{max} [m ³ /h] | H _{max} [m] | P ₀ | L [mm] | W [mm] | H [mm] | Weight [kg] |
|---------|-------------|-----------------------|-----------------------|---------------------------|---|-------------------------|----------------|-----------|-----------|-----------|----------------|
| 18604 | 3~230/3~400 | 2.000 | 6,6/3,8 | 2850 | 8,7 | 62,0 | RP1 | 456 | 154 | 238 | 19,2 |

Characteristics:



Materials:

| | |
|-------------------------|---|
| Material impeller: | stainless steel AISI 304 |
| Seal pump: | mechanical seal carbon/ceramic/Viton |
| Material motor housing: | Light metal L-2521 |
| Material pump housing: | stainless steel AISI 304 |
| Material motor shaft: | stainless steel AISI 316 |

Dimensions:

