

Rain water harvesting Raincenter Comfort 25

incl. fill level indicator with CPS 20-5 MB

Features:

- fully automatic electronic control of the entire installation
- integrated domestic water works CPS 20-5 with automatic control ZP Control 05 Basic
- house-internal drinking water replenishing on demand directly to the pump by-passing the tank

Application:

- compact central unit for automatic control and water supplies from rainwa-ter utilization plants
- multi-apartment houses and similar objects
- clear water without aggressive and abrasive components

Scope of delivery:

- filling level transducer with cable, 25 m long
- wall mounting set including vibration-damping equipment



Product benefits:

- compact and fully automatic rainwater harvesting system with high pumping capacity
- fast installation (plug & pump connect > plug-in > ready)
- wall-mounting for space-saving installation
- low-noise centrifugal pump
- automatic hygiene flush in potable water tank
- version 'Comfort': level indicator via electronic pressure sensor, possibility to connect a feeder pump or backflow monitor

Technical data:

Art.no.	U [V]	P ₁ [W]	In [A]	n [min-1]	Qmax [m³/h]	Hmax [m]	P0	L [mm]	W [mm]	H [mm]	Weight [kg]
19083	230	1.350	6,1	2850	5,2	52,0	RP1	630	630	340	34,5

Characteristics:





Materials:


Material impeller:	stainless steel AISI 304				
Seal motor:	mechanical seal				
Seal pump:	mechanical seal				
Material pump housing:	stainless steel AISI 304				



Rain water harvesting Raincenter Comfort 25

incl. fill level indicator with CPS 20-5 MB

Example of installation:





Rain water harvesting Raincenter Comfort 25

incl. fill level indicator with CPS 20-5 MB

Dimensions:

