

#### Features:

- With ART System (Automatic Reset Test). In case of dry running, the system will automatically stop and periodically re-start
- Automatic recovery of system settings after a power failure
- Built-in pressure transmitter with digital display
- Recording of operations and thus information about operating hours, number of starts, number of power interruptions. Alarm recording: Type and number of alarm messages from the date of commissioning
- STC function (Smart Temperature Control): If the electronics assembly / the converter reaches a temperature of 85°C, the frequency will be slowed. This way, the temperature is decreased, but the water flow is kept.
- Designed for wall mounting
- Pressure sensor included in scope of delivery
- Supply voltage 1x230V (Box MT) or 3x400V (Box TT)
- Control pressure: 0.5 - 10 bar (on request with a different pressure sensor 0.5 - 16 bar)

#### Application:

- Pump control by means of frequency converter. It can control an individual pump or 2 pumps in combination (master-slave mode with alternating pump activation)



#### Product benefits:

- Aluminium heat exchanger
- Control and information panel with LCD screen
- insulation-protected PVC housing IP55
- PG connection with strain relief
- Alarm recording
- Auto-reset function

#### Technical data:

Art.no.	U [V]	L [mm]	W [mm]	H [mm]	Weight [kg]
20296	400	186	173	344	4,75