

Features:

- the on/off control is done automatically by a robust float switch
- in case of pump failure (impermissibly high water level in the tank) an alarm switch can switch off the air conditioner or condensing boiler
- connection for pressure hose with 9 mm inner diameter
- tank volume 1,2 l
- operating temperature maximum 80°C S3 15% (1min 30 in function / 8min 30 stop)
- integrated non-return valve to prevent condensate return
- the device has an inlet with 28 mm diameter, if necessary use adapter DN 19, 32, 40
- System is equipped with wall mounting device


Application:

- drainage of condensation water and condensate from the climate control unit and the gas calorific value boilers with a pH-value up to 2.5

Product benefits:

- including alarm switch
- flexible connection options

Scope of delivery:

- 6 m hose with 9 mm inner diameter
- 2.0 m connection cable with safety plug
- 1,5 m cable for alarm circuit
- 1 inlet spigot
- 1 transition adapter hose /HT DN 50
- mounting screws

Technical data:

Art.no.	U [V]	P ₁ [W]	I _n [A]	Q _{max} [m ³ /h]	H _{max} [m]	L [mm]	W [mm]	H [mm]	Weight [kg]
21842	230	60	0,52	0,34	4,5	287	127	160	2,6

Characteristics:


Dimensions:

